



**SAFETY DATA SHEET**  
151 PAINT BRUSH RESTORER

Page 1  
Issued: 17/10/2005  
Revision No: 1

**1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING**

**Product name:** 151 PAINT BRUSH RESTORER

**Product code:** 00110

**Use / description of product:** Formulated Cleaning Product

**Company name:** 151 Products

Globe House

3rd Floor Southall Street

Manchester

M3 1LG

Tel: 0161 8395949

Fax: 0161 8395493

**2. COMPOSITION / INFORMATION ON INGREDIENTS**

**Hazardous ingredients:** STRAIGHT RUN Kerosine - Kerosine (Petroleum) 30-50%

EINECS: 232-366-4 CAS: 8008-20-6

[Xi] R38; [N] R51/53; [Xn] R65

- DICHLOROMETHANE 10-30%

EINECS: 200-838-9 CAS: 75-09-2

[Xn] R40

- FATTY ALCOHOL ETHOXYLATE 1-10%

CAS: 68439-46-3

[Xn] R22; [Xi] R41; [N] R50

**3. HAZARDS IDENTIFICATION**

**Main hazards:** Irritating to eyes and skin. Harmful: may cause lung damage if swallowed. Limited evidence of a carcinogenic effect. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**4. FIRST AID MEASURES (SYMPTOMS)**

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**4. FIRST AID MEASURES (ACTION)**

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

[cont...]

**SAFETY DATA SHEET**  
151 PAINT BRUSH RESTORER

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

**5. FIRE-FIGHTING MEASURES**

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

**Exposure hazards:** In combustion emits toxic fumes.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**7. HANDLING AND STORAGE**

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Hazardous ingredients:** DICHLOROMETHANE  
WEL (8 hr exposure limit): 350 mg/m<sup>3</sup> WEL (15 min exposure limit): 1060 mg/m<sup>3</sup>

**Engineering measures:** Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Impermeable gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**State:** Liquid

**Viscosity:** Non-viscous

**Flash point°C:** 100**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions.**Conditions to avoid:** Heat.**Materials to avoid:** Strong oxidising agents. Strong acids.**Haz. decomp. products:** In combustion emits toxic fumes.**11. TOXICOLOGICAL INFORMATION****Hazardous ingredients:** STRAIGHT RUN Kerosine - Kerosine (PETROLEUM)

IPR RAT LD50 10700 mg/kg

IPR RBT LD50 6600 mg/kg

ORL RBT LD50 2835 mg/kg

## • DICHLOROMETHANE

ORL MUS LD50 4770 mg/kg

ORL RAT LD50 5350 mg/kg

SCU MUS LD50 6460 mg/kg

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.**12. ECOLOGICAL INFORMATION****Hazardous ingredients:** FATTY ALCOHOL ETHOXYLATE

FISH RAINBOW TROUT 96H LC50 10 mg/l

**Mobility:** Readily absorbed into soil.**Persistence and degradability:** Not biodegradable.**Bioaccumulative potential:** Bioaccumulation potential.**Other adverse effects:** Toxic to aquatic organisms. Toxic to soil organisms.**13. DISPOSAL CONSIDERATIONS****NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID****UN no:** 2810**ADR Class:** 6.1**Packing group:** III**Classification code:** T1**Shipping name:** TOXIC LIQUID, ORGANIC, N.O.S. (DICHLOROMETHANE)**Labelling:** 6.1**Hazard ID no:** 60

**SAFETY DATA SHEET**  
151 PAINT BRUSH RESTORER**IMDG / IMO**

<b>UN no:</b> 2810	<b>Class:</b> 6.1
<b>Packing group:</b> III	<b>EmS:</b> F-A,S-A
<b>Marine pollutant:</b> .	<b>Labelling:</b> 6.1

**IATA / ICAO**

<b>UN no:</b> 2810	<b>Class:</b> 6.1
<b>Packing group:</b> III	<b>Packing instructions:</b> 611(P&CA); 618(CAO)
<b>Labelling:</b> 6.1	

**15. REGULATORY INFORMATION**

**Hazard symbols:** Dangerous for the environment.  
Harmful.



**Risk phrases:** R36/38: Irritating to eyes and skin.  
R65: Harmful: may cause lung damage if swallowed.  
R40: Limited evidence of a carcinogenic effect.  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety phrases:** S2: Keep out of the reach of children.  
S29: Do not empty into drains.  
S24/25: Avoid contact with skin and eyes.  
S36/37: Wear suitable protective clothing and gloves.  
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.  
S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

**16. OTHER INFORMATION**

**Other information:** Product must bear a TACTILE WARNING TRIANGLE measuring 18mm+/- 2mm on normal handling surface. It must also be fitted with a child resistant closure when sold to retail.

**Risk phrases used in s.2:** R38: Irritating to skin.  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**SAFETY DATA SHEET**  
151 PAINT BRUSH RESTORER

R65: Harmful: may cause lung damage if swallowed.

R40: Limited evidence of a carcinogenic effect.

R22: Harmful if swallowed.

R41: Risk of serious damage to eyes.

R50: Very toxic to aquatic organisms.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.