



SAFETY DATA SHEET
INTERIOR CLEAN AND SHINE

Page 1
Issued: 13/07/2005
Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: INTERIOR CLEAN AND SHINE

Product code: 00431

Use / description of product: Formulated Dashboard Shine

Company name: 151 Products

Globe House

3rd Floor Southall Street

Manchester

M3 1LG

Tel: 0161 8395949

Fax: 0161 8395493

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: LIQUID PETROLEUM GAS 10-30%

EINECS: 270-990-9 CAS: 68512-91-4

[F+] R12

- LOW BOILING POINT MODIFIED NAPHTHA - NAPHTHA (PETROLEUM),
SOLVENT-REFINED LIGHT 50-70%

EINECS: 265-086-6 CAS: 64741-84-0

[F+] R12; [Xi] R38; [N] R51/53; [Xn] R65

- PROPAN-2-OL <1%

EINECS: 200-661-7 CAS: 67-63-0

[F] R11; [Xi] R36; [-] R67

Contains: Silicone oil.

3. HAZARDS IDENTIFICATION

Main hazards: Extremely flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

[cont...]

SAFETY DATA SHEET
INTERIOR CLEAN AND SHINE

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not create dust.

Environmental precautions: Do not discharge into drains or rivers.

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of dust in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: LIQUID PETROLEUM GAS

WEL (8 hr exposure limit): 1450 mg/m³

- PROPAN-2-OL

WEL (8 hr exposure limit): 999 mg/m³ WEL (15 min exposure limit): 1250 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Respiratory protective device with particle filter.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Aerosol

Flash point°C: -20

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: PROPAN-2-OL
IVN RAT LD50 1088 mg/kg
ORL MUS LD50 3600 mg/kg
ORL RAT LD50 5045 mg/kg
SCU MUS LDLO 6 gm/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Not biodegradable.

Bioaccumulative potential: Bioaccumulation potential.

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Disposal should be in accordance with Local Authority regulations

Disposal of packaging: Used containers must not be cut up or punctured until completely purged of product residues
Disposal should be in accordance with Local Authority regulations

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1950

ADR Class: 2

Classification code: 5F

Shipping name: AEROSOLS

Labelling: 2.1



SAFETY DATA SHEET
INTERIOR CLEAN AND SHINE

IMDG / IMO

UN no: 1950	Class: 2
EmS: F-D,S-U	Marine pollutant: .
Labelling: 2.1	

IATA / ICAO

UN no: 1950	Class: 2
Labelling: 2.1	

15. REGULATORY INFORMATION

Hazard symbols: Extremely flammable.
Dangerous for the environment.



Risk phrases: R12: Extremely flammable.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S2: Keep out of the reach of children.
S29: Do not empty into drains.
S51: Use only in well-ventilated areas.
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R12: Extremely flammable.
R38: Irritating to skin.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65: Harmful: may cause lung damage if swallowed.
R11: Highly flammable.
R36: Irritating to eyes.
R67: Vapours may cause drowsiness and dizziness.

SAFETY DATA SHEET
INTERIOR CLEAN AND SHINE

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.