



SAFETY DATA SHEET
PUNCTURE REPAIR AEROSOL

Page 1
Issued: 12/03/2007
Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: PUNCTURE REPAIR AEROSOL
Use / description of product: Puncture Repair aerosol
Company name: 151 Products
Globe House
3rd Floor Southall Street
Manchester
M3 1LG
Tel: 0161 8395949
Fax: 0161 8395493

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: LIQUID PETROLEUM GAS 30-50%
EINECS: 270-990-9 CAS: 68512-91-4
[F+] R12
• AMMONIA, ANHYDROUS <1%
EINECS: 231-635-3 CAS: 7664-41-7
[-] R10; [T] R23; [C] R34; [N] R50
Contains: Polychlorobutadiene

3. HAZARDS IDENTIFICATION

Main hazards: Extremely flammable. Irritating to skin.
Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.
Eye contact: There may be irritation and redness.
Ingestion: There may be irritation of the throat.
Inhalation: There may be a feeling of tightness in the chest with shortness of breath.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.
Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion: Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

SAFETY DATA SHEET
PUNCTURE REPAIR AEROSOL**5. FIRE-FIGHTING MEASURES**

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Do not use equipment in clean-up procedure which may produce sparks. Absorb into dry earth or sand. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

7. HANDLING AND STORAGE

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: LIQUID PETROLEUM GAS
WEL (8 hr exposure limit): 1450 mg/m³

- AMMONIA, ANHYDROUS
WEL (8 hr exposure limit): 18 mg/m³ WEL (15 min exposure limit): 25 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required. Ensure adequate ventilation.

Hand protection: Avoid skin contact or wear gloves if necessary.

Eye protection: Avoid contact with eyes - refer to section 4.

Skin protection: Avoid skin contact or wear gloves if necessary.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Aerosol

Colour: Off-white

SAFETY DATA SHEET
PUNCTURE REPAIR AEROSOL**Odour:** Perceptible odour**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions. Stable at room temperature.**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.**Materials to avoid:** Strong oxidising agents. Strong acids.**Haz. decomp. products:** In combustion emits toxic fumes.**11. TOXICOLOGICAL INFORMATION****Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.**12. ECOLOGICAL INFORMATION****Mobility:** Readily absorbed into soil.**Persistence and degradability:** Biodegradable.**Bioaccumulative potential:** No bioaccumulation potential.**Other adverse effects:** Negligible ecotoxicity.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** Disposal should be in accordance with Local Authority regulations**Disposal of packaging:** Used containers must not be cut up or punctured until completely purged of product residues
Contact local authority for location of nearest aerosol recycling bin. Disposal should be in accordance with Local Authority regulations**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID****UN no:** 1950**ADR Class:** 2**Classification code:** 5F**Shipping name:** AEROSOLS**Labelling:** 2.1**IMDG / IMO****UN no:** 1950**Class:** 2**EmS:** F-D,S-U**Marine pollutant:** .**Labelling:** 2.1

SAFETY DATA SHEET
PUNCTURE REPAIR AEROSOL

IATA / ICAO

UN no: 1950

Class: 2

Labelling: 2.1

15. REGULATORY INFORMATION

Hazard symbols: Highly flammable.



Risk phrases: R12: Extremely flammable.

R38: Irritating to skin.

Safety phrases: S2: Keep out of the reach of children.

S24: Avoid contact with skin.

S46: If swallowed, seek medical advice immediately and show this container or label.

S51: Use only in well-ventilated areas.

S23: Do not breathe spray

S35: This material and its container must be disposed of in a safe way.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R12: Extremely flammable.

R10: Flammable.

R23: Toxic by inhalation.

R34: Causes burns.

R50: Very toxic to aquatic organisms.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.