



## SAFETY DATA SHEET

VARNISH - MAHOGANY

Page 1

Issued: 11/02/2005

Revision No: 1

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** VARNISH - MAHOGANY

**Product code:** DY009

**Use / description of product:** A Polyurethane Modified long oil Alkyd resin based Varnish

**Company name:** 151 Products

Globe House

3rd Floor Southall Street

Manchester

M3 1LG

Tel: 0161 8395949

Fax: 0161 8395493

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

**Hazardous ingredients:** STRAIGHT RUN KEROSENE - SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH.

30-50%

EINECS: 265-191-7 CAS: 64742-88-7

[Xn] R65; [Xi] R38; [N] R51/53

- 1,2,4-TRIMETHYLBENZENE 1-10%

EINECS: 202-436-9 CAS: 95-63-6

[-] R10; [Xn] R20; [Xi] R36/37/38; [N] R51/53

- MESITYLENE 1-10%

EINECS: 203-604-4 CAS: 108-67-8

[-] R10; [Xi] R37; [N] R51/53

- CUMENE <1%

EINECS: 202-704-5 CAS: 98-82-8

[-] R10; [Xi] R37; [N] R51/53; [Xn] R65

- XYLENE 1-10%

EINECS: 215-535-7 CAS: 1330-20-7

[-] R10; [Xn] R20/21; [Xi] R38

### 3. HAZARDS IDENTIFICATION

**Main hazards:** Flammable. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

### 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

[cont...]

**SAFETY DATA SHEET**

VARNISH - MAHOGANY

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**4. FIRST AID MEASURES (ACTION)**

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

**5. FIRE-FIGHTING MEASURES**

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

**Exposure hazards:** In combustion emits toxic fumes.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**7. HANDLING AND STORAGE**

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Hazardous ingredients:** 1,2,4-TRIMETHYLBENZENE

WEL (8 hr exposure limit): 100 mg/m<sup>3</sup> WEL (15 min exposure limit): 200 mg/m<sup>3</sup>

- MESITYLENE

WEL (8 hr exposure limit): 25 ppm

- CUMENE

WEL (8 hr exposure limit): 125 mg/m<sup>3</sup> WEL (15 min exposure limit): 250 mg/m<sup>3</sup>

**SAFETY DATA SHEET**

VARNISH - MAHOGANY

- XYLENE

WEL (8 hr exposure limit): 220 mg/m<sup>3</sup> WEL (15 min exposure limit): 441 mg/m<sup>3</sup>

**Engineering measures:** Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Impermeable gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**State:** Liquid

**Colour:** Colourless

**Solubility in water:** Insoluble

**Viscosity:** Highly viscous

**Viscosity test method:** Flow time in seconds in a 3 mm ISO cup (ISO 2431)

**Flash point°C:** 41

**10. STABILITY AND REACTIVITY**

**Stability:** Stable under normal conditions.

**Conditions to avoid:** Heat.

**Materials to avoid:** Strong oxidising agents. Strong acids.

**Haz. decomp. products:** In combustion emits toxic fumes.

**11. TOXICOLOGICAL INFORMATION**

**Hazardous ingredients:** 1,2,4-TRIMETHYLBENZENE

IPR RAT LDLO 1752 mg/kg

ORL RAT LD50 5 gm/kg

- MESITYLENE

IPR GPG LDLO 1303 mg/kg

- CUMENE

ORL MUS LD50 12750 mg/kg

ORL RAT LD50 1400 mg/kg

- XYLENE

ORL MUS LD50 2119 mg/kg

ORL RAT LD50 4300 mg/kg

SCU RAT LD50 1700 mg/kg

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

## SAFETY DATA SHEET

VARNISH - MAHOGANY

### 12. ECOLOGICAL INFORMATION

- Mobility:** Readily absorbed into soil.
- Persistence and degradability:** Not biodegradable.
- Bioaccumulative potential:** Bioaccumulation potential.
- Other adverse effects:** Toxic to aquatic organisms. Toxic to soil organisms.

### 13. DISPOSAL CONSIDERATIONS

- Disposal operations:** Disposal should be in accordance with Local Authority regulations
- Disposal of packaging:** Disposal should be in accordance with Local Authority regulations
- NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

### 14. TRANSPORT INFORMATION

#### ADR / RID

- |                             |                                |
|-----------------------------|--------------------------------|
| <b>UN no:</b> 1263          | <b>ADR Class:</b> 3            |
| <b>Packing group:</b> III   | <b>Classification code:</b> F1 |
| <b>Shipping name:</b> PAINT |                                |
| <b>Labelling:</b> 3         | <b>Hazard ID no:</b> 30        |



#### IMDG / IMO

- |                            |                      |
|----------------------------|----------------------|
| <b>UN no:</b> 1263         | <b>Class:</b> 3      |
| <b>Packing group:</b> III  | <b>EmS:</b> F-E,S-E* |
| <b>Marine pollutant:</b> . | <b>Labelling:</b> 3  |

#### IATA / ICAO

- |                           |  |
|---------------------------|--|
| <b>UN no:</b> 1263        | <b>Class:</b> 3                                  |
| <b>Packing group:</b> III | <b>Packing instructions:</b> 309(P&CA); 310(CAO) |
| <b>Labelling:</b> 3       |  |

### 15. REGULATORY INFORMATION

- Hazard symbols:** Irritant.  
Dangerous for the environment.



- Risk phrases:** R10: Flammable.

**SAFETY DATA SHEET**  
VARNISH - MAHOGANY

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety phrases:** S2: Keep out of the reach of children.

S29: Do not empty into drains.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

**16. OTHER INFORMATION**

**Risk phrases used in s.2:** R65: Harmful: may cause lung damage if swallowed.

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R10: Flammable.

R20: Harmful by inhalation.

R36/37/38: Irritating to eyes, respiratory system and skin.

R37: Irritating to respiratory system.

R20/21: Harmful by inhalation and in contact with skin.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.