



**SAFETY DATA SHEET**  
RAC INTERIOR DASH CLEANER

Page 1  
Issued: 11/01/2006  
Revision No: 1

**1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING**

**Product name:** RAC INTERIOR DASH CLEANER

**Product code:** RACOF015

**Use / description of product:** Formulated Dashboard Shine

**Company name:** 151 Products

Globe House

3rd Floor Southall Street

Manchester

M3 1LG

Tel: 0161 8395949

Fax: 0161 8395493

**2. COMPOSITION / INFORMATION ON INGREDIENTS**

**Hazardous ingredients:** LIQUID PETROLEUM GAS 10-30%

EINECS: 270-990-9 CAS: 68512-91-4

[F+] R12

- LOW BOILING POINT MODIFIED NAPHTHA - NAPHTHA (PETROLEUM),

SOLVENT-REFINED LIGHT 30-50%

EINECS: 265-086-6 CAS: 64741-84-0

[F+] R12; [Xi] R38; [N] R51/53; [Xn] R65

- PROPAN-2-OL 1-10%

EINECS: 200-661-7 CAS: 67-63-0

[F] R11; [Xi] R36; [-] R67

**Contains:** Silicone oil.

**3. HAZARDS IDENTIFICATION**

**Main hazards:** Extremely flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**4. FIRST AID MEASURES (SYMPTOMS)**

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**4. FIRST AID MEASURES (ACTION)**

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

[cont...]

## SAFETY DATA SHEET

RAC INTERIOR DASH CLEANER

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 5. FIRE-FIGHTING MEASURES

**Extinguishing media:** Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

**Exposure hazards:** Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

### 7. HANDLING AND STORAGE

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Hazardous ingredients:** LIQUID PETROLEUM GAS  
WEL (8 hr exposure limit): 1450 mg/m<sup>3</sup>

- PROPAN-2-OL  
WEL (8 hr exposure limit): 999 mg/m<sup>3</sup> WEL (15 min exposure limit): 1250 mg/m<sup>3</sup>

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**9. PHYSICAL AND CHEMICAL PROPERTIES****State:** Aerosol**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions. Stable at room temperature.**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.**Materials to avoid:** Strong oxidising agents. Strong acids.**Haz. decomp. products:** In combustion emits toxic fumes.**11. TOXICOLOGICAL INFORMATION****Hazardous ingredients:** PROPAN-2-OL  
IVN RAT LD50 1088 mg/kg  
ORL MUS LD50 3600 mg/kg  
ORL RAT LD50 5045 mg/kg  
SCU MUS LDLO 6 gm/kg**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.**12. ECOLOGICAL INFORMATION****Mobility:** Readily absorbed into soil.**Persistence and degradability:** Biodegradable.**Bioaccumulative potential:** No bioaccumulation potential.**Other adverse effects:** Negligible ecotoxicity.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** Disposal should be in accordance with Local Authority regulations**Disposal of packaging:** Used containers must not be cut up or punctured until completely purged of product residues  
Disposal should be in accordance with Local Authority regulations**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID****UN no:** 1950**ADR Class:** 2**Classification code:** 5F**Shipping name:** AEROSOLS**Labelling:** 2.1

**SAFETY DATA SHEET**  
RAC INTERIOR DASH CLEANER**IMDG / IMO**

**UN no:** 1950 **Class:** 2  
**EmS:** F-D,S-U **Marine pollutant:** .  
**Labelling:** 2.1

**IATA / ICAO**

**UN no:** 1950 **Class:** 2  
**Labelling:** 2.1

**15. REGULATORY INFORMATION**

**Hazard symbols:** Extremely flammable.



**Risk phrases:** R12: Extremely flammable.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety phrases:** S2: Keep out of the reach of children.

S51: Use only in well-ventilated areas.

S46: If swallowed, seek medical advice immediately and show this container or label.

**Precautionary phrases:** Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

**16. OTHER INFORMATION**

**Risk phrases used in s.2:** R12: Extremely flammable.

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R11: Highly flammable.

R36: Irritating to eyes.

R67: Vapours may cause drowsiness and dizziness.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall

**SAFETY DATA SHEET**  
RAC INTERIOR DASH CLEANER

be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.