

151 WHITE SPIRIT

Page: 1

Compilation date: 30/03/2012

Revision date: 09/05/2018

Revision No: 5

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: 151 WHITE SPIRIT

REACH registered number(s): 01-2119458049-33-XXXX

CAS number: 64742-82-1
EINECS number: 919-446-0
Product code: 00013

Synonyms: HYDROCARBONS C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC9a: Coatings and paints, thinners, paint removers. SU 21 - Consumer Uses.

1.3. Details of the supplier of the safety data sheet

Company name: 151 Products Limited

The Old School House 39 Bengal Street Manchester

M4 6AF

UK

Tel: 0161 839 5949 **Fax:** 0161 839 5493

Email: fereshteh@151.co.uk

1.4. Emergency telephone number

Emergency tel: 0161 839 5949 (08:00 - 17:30)

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT RE 1: H372; STOT

SE 3: H336; -: EUH066

Most important adverse effects: Repeated exposure may cause skin dryness or cracking. Flammable liquid and vapour.

May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Causes damage to organs the central nervous system (CNS) through prolonged or repeated exposure inhalation (vapour). Toxic to aquatic life with long lasting effects.

151 WHITE SPIRIT

Page: 2

2.2. Label elements

Label elements:

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H336: May cause drowsiness or dizziness.

H372: Causes damage to organs the central nervous system (CNS) through prolonged

or repeated exposure inhalation (vapour).

H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark GHS08: Health hazard GHS09: Environmental









Signal words: Danger

Precautionary statements: * P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P103: Read label before use.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P260: Do not breathe fumes & vapours.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves, protective clothing & eye protection.

P301+310: IF SWALLOWED: Immediately call a.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water shower.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P314: Get medical advice if you feel unwell.

P331: Do NOT induce vomiting.

P403+233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents/container to Local Authority regulations.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

151 WHITE SPIRIT

Page: 3

Section 3: Composition/information on ingredients

3.1. Substances

Chemical identity: HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)

CAS number: 64742-82-1 **EINECS number:** 919-446-0

REACH registered number(s): 01-2119458049-33-XXXX

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still

on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact. Prolonged or repeated

exposure may cause drying/defatting of the skin.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: Inhalation may have a narcotic effect, cause irritation of the respiratory tract, headache

and drowsiness and other effects to the CNS.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes. Vapours are heavier than air and may spread near the

ground and travel a considerable distance to a source of ignition and flash back.

151 WHITE SPIRIT

Page: 4

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area

with signs and prevent access to unauthorised personnel. Turn leaking containers

leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. KEEP OUT OF THE

REACH OF CHILDREN.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

Hazardous ingredients:

151 WHITE SPIRIT

Page: 5

HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)

Type	Exposure	Value	Population	Effect
DNEL	Inhalation (Long term)	330mg/m ³	Workers	Systemic
DNEL	Inhalation (Acute)	570mg/m ³	Workers	Systemic
DNEL	Dermal	21mg/kg	Workers	Systemic
DNEL	Inhalation (Long term)	71mg/m³	General Population	Systemic
DNEL	Inhalation (Acute)	570mg/m³	General Population	Systemic
DNEL	Dermal	12mg/kg	General Population	Systemic
DNEL	Oral (Long term)	21mg/kg	General Population	Systemic

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves. It is recommended to check the resistance to chemicals of the

protective gloves mentioned together with the supplier of the gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colourless

Odour: Characteristic odour

Solubility in water: Not miscible

Viscosity: Non-viscous Kinematic viscosity: 0.95m2/s

Boiling point/range°C: 150-200 Flammability limits %: lower: 0.7

upper: 7 Flash point°C: 38

Autoflammability°C: >230 Vapour pressure: <5kPa

Relative density: 0.774-0.795

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

151 WHITE SPIRIT

Page: 6

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)

DERMAL	RAT	LD50	>3400	mg/kg
ORAL	RAT	LD50	>15000	mg/kg
VAPOURS	RAT	4H LC50	>13100	mg/m3

Relevant hazards for product:

Hazard	Route	Basis
STOT-single exposure	-	Hazardous: calculated
STOT-repeated exposure	-	Based on test data
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact. Prolonged or repeated

exposure may cause drying/defatting of the skin.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: Inhalation may have a narcotic effect, cause irritation of the respiratory tract, headache

and drowsiness and other effects to the CNS.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

151 WHITE SPIRIT

Page: 7

Ecotoxicity values:

Species	Test	Value	Units
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	10-30	mg/l
Daphnia magna	48H EC50	10-22	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H ErC50	4.1	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	LOEC 21 Days	0.13	mg/l
Daphnia magna	LOEC 21 Days	0.28	mg/l

Hazardous ingredients:

HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)

Daphnia magna	48H EC50	22	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	30	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Data on hydrocarbons UVCB substances are not meaningful.

12.4. Mobility in soil

Mobility: UVCB Substance, standard tests for this endpoint are not appropriate.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Waste code number: 08 01 11

Disposal of packaging: Disposal should be in accordance with Local Authority Regulations.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1300

151 WHITE SPIRIT

Page: 8

14.2. UN proper shipping name

Shipping name: TURPENTINE SUBSTITUTE (WHITE SPIRIT)

(HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-

25%))

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E
Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has been carried out for the substance or the mixture by

the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H336: May cause drowsiness or dizziness.

H372: Causes damage to organs <or state all organs affected, if known> through

prolonged or repeated exposure <state route of exposure if it is conclusively proven that

no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.