

151 FAST ADHESIVE GLUE & ACCELERATOR (ACTIVATOR)

Page: 1

Compilation date: 30/05/2018

Revision No: 1

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: 151 FAST ADHESIVE GLUE & ACCELERATOR (ACTIVATOR)

Product code: 151050

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: SU 21 - Consumer Uses. PC1: Adhesives, sealants.

# 1.3. Details of the supplier of the safety data sheet

Company name: 151 Products Limited

The Old School House

39 Bengal Street

Manchester

M4 6AF

UK

Tel: 0161 839 5949

Fax: 0161 839 5493

Email: fereshteh@151.co.uk

### 1.4. Emergency telephone number

Emergency tel: 0161 839 5949 (08:00 - 17:30)

(office hours only)

### **Section 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 2: H411; Flam. Aerosol 1: H222; Repr. 2: H361; Skin Irrit. 2: H315; STOT

RE 2: H373; STOT SE 3: H336; -: H229

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin

irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

#### Label elements:

Hazard statements: H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H361: Suspected of damaging fertility or the unborn child.

151 FAST ADHESIVE GLUE & ACCELERATOR (ACTIVATOR)

Page: 2

H373: May cause damage to organs through prolonged or repeated exposure.

H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark GHS08: Health hazard GHS09: Environmental









Signal words: Danger

**Precautionary statements:** P102: Keep out of reach of children.

P103: Read label before use.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P261: Avoid breathing vapours.

P264: Wash hands thoroughly after handling.

P308+P313: IF exposed or concerned: Get medical advice.

P101: If medical advice is needed, have product container or label at hand.

P403: Store in a well-ventilated place.

P501: Dispose of contents and container to Local authority regulations.

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

### Section 3: Composition/information on ingredients

#### 3.2. Mixtures

### **Hazardous ingredients:**

HYDROCARBONS, C6, N-ALKANES, ISOALKANES, CYCLICS, N-HEXANE RICH

EINECS	CAS	PBT / WEL	CLP Classification	Percent
925-292-5	-	-	Flam. Liq. 2: H225; Repr. 2: H361; STOT SE 3: H336; STOT RE 2: H373; Skin Irrit. 2: H315; Asp. Tox. 1: H304; Aquatic Chronic 2: H411	25-50%

151 FAST ADHESIVE GLUE & ACCELERATOR (ACTIVATOR)

Page: 3

ΒU	JΤΑ	NE

20171112				
203-448-7	106-97-8	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-25%
ISOBUTANE				
200-857-2	75-28-5	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-25%
PROPANE				
200-827-9	74-98-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	5-10%
N,N-DIMETH	YL-P-TOLUIDIN	NE		
202-805-4	99-97-8	-	Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT RE 2: H373; Aquatic Chronic 3: H412	<1%

### Section 4: First aid measures

### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Get medical attention.

Ingestion: Wash out mouth with water. Do not induce vomiting. If you feel unwell seek medical

attention

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor. Solvent abuse can kill.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

 $\label{logistion:logistical} \textbf{Ingestion:} \ \ \textbf{There may be soreness and redness of the mouth and throat.}$ 

Inhalation: Exposure may cause coughing or wheezing. Solvent abuse can kill.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# 4.3. Indication of any immediate medical attention and special treatment needed

### Section 5: Fire-fighting measures

# 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes. Vapour may travel considerable distance to source of

ignition and flash back. Pressurized container may explode in the heat of a fire.

151 FAST ADHESIVE GLUE & ACCELERATOR (ACTIVATOR)

Page: 4

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-

side up to prevent the escape of liquid.

### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

## Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. KEEP OUT OF THE REACH OF CHILDREN.

Suitable packaging: Must only be kept in original packaging.

#### 7.3. Specific end use(s)

Specific end use(s): No data available.

#### Section 8: Exposure controls/personal protection

# 8.1. Control parameters

#### **Hazardous ingredients:**

#### HYDROCARBONS, C6, N-ALKANES, ISOALKANES, CYCLICS, N-HEXANE RICH

# Workplace exposure limits:

# Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	20ppm	-	-	-

#### **DNEL/PNEC Values**

151 FAST ADHESIVE GLUE & ACCELERATOR (ACTIVATOR)

Page: 5

#### **Hazardous ingredients:**

#### HYDROCARBONS, C6, N-ALKANES, ISOALKANES, CYCLICS, N-HEXANE RICH

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	93mg/m³	Workers	Systemic
DNEL	Dermal	13mg/kg bw	Workers	Systemic
DNEL	Inhalation	20mg/m³	General Population	Systemic
DNEL	Dermal	7mg/kg bw	General Population	Systemic
DNEL	Oral	6mg/kg bw	General Population	Systemic

#### 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required. In case of insufficient ventilation, wear an approved

respirator gas/vapour filter Type A, organic vapours (EN141).

Hand protection: Protective gloves.Eye protection: Safety glasses.Skin protection: Protective clothing.

# Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Colourless

Odour: Characteristic odour

#### 9.2. Other information

Other information: No data available.

### Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

# 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

## 10.4. Conditions to avoid

Conditions to avoid: Heat. Flames. Sources of ignition.

#### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

151 FAST ADHESIVE GLUE & ACCELERATOR (ACTIVATOR)

Page: 6

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

# **Section 11: Toxicological information**

#### 11.1. Information on toxicological effects

# **Hazardous ingredients:**

# HYDROCARBONS, C6, N-ALKANES, ISOALKANES, CYCLICS, N-HEXANE RICH

DERMAL	RBT	LD50	>5	ml/kg
ORAL	RAT (Male)	LD50	>25	ml/kg
VAPOURS	RBT	4H LC50	73,680	ppm

#### N,N-DIMETHYL-P-TOLUIDINE

IPR	MUS	LDEO	212	ma/ka
IPK	MUS	LD50	212	тід/кд

### Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Reproductive toxicity		Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

### **Excluded hazards for substance:**

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	-	No hazard: calculated
Acute toxicity (ac. tox. 3)	-	No hazard: calculated
Acute toxicity (ac. tox. 2)	-	No hazard: calculated
Acute toxicity (ac. tox. 1)	-	No hazard: calculated
Serious eye damage/irritation	-	No hazard: calculated
Respiratory/skin sensitisation	-	No hazard: calculated
Germ cell mutagenicity	-	No hazard: calculated
Carcinogenicity	-	No hazard: calculated
Aspiration hazard	-	No hazard: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing. Solvent abuse can kill.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

151 FAST ADHESIVE GLUE & ACCELERATOR (ACTIVATOR)

Page: 7

### **Section 12: Ecological information**

### 12.1. Toxicity

## Hazardous ingredients:

#### HYDROCARBONS, C6, N-ALKANES, ISOALKANES, CYCLICS, N-HEXANE RICH

FISH (QSAR) 96H LC50 13.37 mg/l

### 12.2. Persistence and degradability

Persistence and degradability: No data available.

### 12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

### 12.4. Mobility in soil

Mobility: Insoluble in water.

#### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

# Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Disposal operations: Disposal should be in accordance with Local Authority Regulations. Do not pierce

containers prior to disposal.

Disposal of packaging: Disposal should be in accordance with Local Authority Regulations. Do not pierce

containers prior to disposal.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

# **Section 14: Transport information**

# 14.1. UN number

UN number: UN1950

#### 14.2. UN proper shipping name

Shipping name: AEROSOLS

(LPG, PROPANE / BUTANE PRESSURISED LIQUID)

## 14.3. Transport hazard class(es)

Transport class: 2.1

151 FAST ADHESIVE GLUE & ACCELERATOR (ACTIVATOR)

Page: 8

### 14.4. Packing group

#### 14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

### Section 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

#### Section 16: Other information

#### Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation

(EU) 2015/830

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

H229: Pressurised container: May burst if heated.

H301: Toxic if swallowed.

H304: May be fatal if swallowed and enters airways.

H311: Toxic in contact with skin.

H315: Causes skin irritation.

H331: Toxic if inhaled.

H336: May cause drowsiness or dizziness.

H361: {{{0|||message=Suspected of damaging fertility or the unborn child <state specific effect if known>|||default=Suspected of damaging fertility or the unborn child|||filter=(\_)?

H\_361.+}}} ({{{1|||message=<state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>|||filter=(\_)?EXP\_ROUTE\_.+}}}).

H373: May cause damage to organs ( $\{\{0|||message=< or state all organs affected, if known>|||filter=(_)?ORGAN_.+\}\}\}$ ) through prolonged or repeated exposure ( $\{\{\{1|||message=< state route of exposure if it is conclusively proven that no other routes of$ 

H411: Toxic to aquatic life with long lasting effects.

exposure cause the hazard>|||filter=(\_)?EXP\_ROUTE\_.+}}}).

H412: Harmful to aquatic life with long lasting effects.

151 FAST ADHESIVE GLUE & ACCELERATOR (ACTIVATOR)

Page: 9

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.