

CAR PRIDE CHROME POLISH

Page: 1

Compilation date: 12/02/2015

Revision date: 19/11/2014

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: CAR PRIDE CHROME POLISH

Product code: CP1178

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: * SU 21 - Consumer Uses.

PC31: Polishes and wax blends.

1.3. Details of the supplier of the safety data sheet

Company name: 151 Products Limited

The Old School House

39 Bengal Street

Manchester

- M4 6AF
- UK

Tel: 0161 839 5949

- Fax: 0161 839 5493
- Email: fereshteh@151.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: This product has no classification under CLP.

2.2. Label elements

Label elements under CLP:

Precautionary statements: P102: Keep out of reach of children.

P103: Read label before use.

P264: Wash hands thoroughly after handling.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

CAR PRIDE CHROME POLISH

Page: 2

Hazardous ingredients:

TALCUM

238-877-914807-96-6Substance with a Community workplace exposure limitKAOLIN310-194-11332-58-7Substance with a Community workplace exposure limitDISTILLATES (PETROLEUM) HYDROTREATED LIGHT265-149-864742-47-8Substance with a Community workplace exposure limit.Asp. Tox. 1: H304; STOT SE 3: H336; -: EUH066COCAMIDE DEA271-657-068603-42-9-Skin Irrit. 2: H315; Eye Irrit. 2: H319C13-14 ISOPARAFFIN					
workplace exposure limit.KAOLIN310-194-11332-58-7Substance with a Community workplace exposure limitDISTILLATES (PETROLEUM) HYDROTREATED LIGHT265-149-864742-47-8Substance with a Community workplace exposure limit.Asp. Tox. 1: H304; STOT SE 3: H336; -: EUH066COCAMIDE DEA271-657-068603-42-9-Skin Irrit. 2: H315; Eye Irrit. 2: H319C13-14 ISOPARAFFIN	EINECS	CAS	CHIP Classification	CLP Classification	Percent
310-194-11332-58-7Substance with a Community workplace exposure limitDISTILLATES (PETROLEUM) HYDROTREATED LIGHT265-149-864742-47-8Substance with a Community workplace exposure limit.Asp. Tox. 1: H304; STOT SE 3: H336; -: EUH066COCAMIDE DEA271-657-068603-42-9-Skin Irrit. 2: H315; Eye Irrit. 2: H319C13-14 ISOPARAFFIN	238-877-9	14807-96-6		-	10-30%
workplace exposure limit. DISTILLATES (PETROLEUM) HYDROTREATED LIGHT 265-149-8 64742-47-8 Substance with a Community workplace exposure limit. Asp. Tox. 1: H304; STOT SE 3: H336; -: EUH066 COCAMIDE DEA 271-657-0 68603-42-9 - C13-14 ISOPARAFFIN	KAOLIN				
workplace exposure limit. EUH066 COCAMIDE DEA 271-657-0 68603-42-9 - Skin Irrit. 2: H315; Eye Irrit. 2: H319 C13-14 ISOPARAFFIN - - - -	310-194-1	1332-58-7		-	10-30%
workplace exposure limit. EUH066 COCAMIDE DEA 271-657-0 68603-42-9 - Skin Irrit. 2: H315; Eye Irrit. 2: H319 C13-14 ISOPARAFFIN	DISTILLATES ((PETROLEUM) F	HYDROTREATED LIGHT		
271-657-0 68603-42-9 - Skin Irrit. 2: H315; Eye Irrit. 2: H319 C13-14 ISOPARAFFIN	265-149-8	64742-47-8			1-10%
C13-14 ISOPARAFFIN	COCAMIDE DE	ĒA			
	271-657-0	68603-42-9	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319	1-10%
- 246538-79-4 - Aquatic Chronic 2: H411: Acute Tox 3:	C13-14 ISOPAI	RAFFIN			
	-	246538-79-4	-	Aquatic Chronic 2: H411; Acute Tox. 3:	<1%

H331; Asp. Tox. 1: H304

Section 4: First aid measures

4.1. Description of first aid me	easures			
Skin contact:	Wash immediately with plenty of soap and water.			
Eye contact:	Bathe the eye with running water for 15 minutes. If irritation persists seek medical			
	advice.			
Ingestion:	Do not induce vomiting. Wash out mouth with water. If patient feels unwell seek medical			
	attention			
Inhalation:	Move to fresh air in case of accidental inhalation of vapours.			
4.2. Most important symptoms and effects, both acute and delayed				
Skin contact:	There may be mild irritation at the site of contact.			
Eye contact:	There may be irritation and redness.			
Ingestion:	There may be irritation of the throat.			
Inhalation:	There may be irritation of the nose and upper respiratory tract.			
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.			

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

CAR PRIDE CHROME POLISH

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a suitable container. Wash the spillage site with large amounts of water.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep out of the reach of children.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

TALCUM

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1mg/m3	-	-	-

CAR PRIDE CHROME POLISH

					raye. 4
KAOLIN					
UK	2mg/m3	-		-	-
DISTILLATES (PETROLEUM	I) HYDROTREAT	ED LIGHT			
EU 2	00mg/m3	-		-	-
DNEL/PNEC Values					
	No data available). 			
8.2. Exposure controls					
Engineering measures:	Ensure there is s	ufficient ventilation	of the area.		
Respiratory protection:	No special requir	ements under norm	nal conditions of	use.	
Hand protection:					
		ements under norm			
Skin protection:	No special requir	ements under norn	nal conditions of	use.	
ction 9: Physical and cher	nical properties	;			
9.1. Information on basic phy	sical and chemic	al properties			
State:	Paste				
Colour:	Beige				
Odour:	Perceptible odou	r			
Solubility in water:	Insoluble				
Flash point°C:	>76		R	elative density: 1.05 -	1.15
pH:	9.0 - 10.5				
9.2. Other information					
Other information:	No data available).			
ection 10: Stability and read	ctivity				
10.1. Reactivity					
Reactivity:	Stable under reco	ommended transpo	rt or storage con	ditions.	
10.2. Chemical stability					
Chemical stability:	Stable under nor	mal conditions.			

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

Page: 4

CAR PRIDE CHROME POLISH

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

DISTILLATES (PETROLEUM) HYDROTREATED LIGHT

DERMAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg
VAPOURS	RAT	4H LC50	>5.28	mg/l

COCAMIDE DEA

ORAL RAT LD50 >3000 mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the nose and upper respiratory tract.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable in part only.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

CAR PRIDE CHROME POLISH

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Disposal should be in accordance with Local Authority Regulations.

Disposal of packaging: Disposal should be in accordance with Local Authority Regulations.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: A REACH registration number is not applicable as this product is a mixture.

15.2. Chemical Safety Assessment

Section 16: Other information

	This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010. * indicates text in the SDS which has changed since the last revision.
	* indicates text in the SDS which has changed since the last revision.
	······································
Phrases used in s.2 and s.3:	EUH066: Repeated exposure may cause skin dryness or cracking.
	H304: May be fatal if swallowed and enters airways.
	H315: Causes skin irritation.
	H319: Causes serious eye irritation.
	H331: Toxic if inhaled.
	H336: May cause drowsiness or dizziness.
	H411: Toxic to aquatic life with long lasting effects.
Legend to abbreviations:	PNEC = predicted no effect level
	DNEL = derived no effect level
	LD50 = median lethal dose
	LC50 = median lethal concentration
	EC50 = median effective concentration
	IC50 = median inhibitory concentration
	dw = dry weight
	bw = body weight

CAR PRIDE CHROME POLISH

Page: 7

 cc = closed cup

 oc = open cup

 MUS = mouse

 GPG = guinea pig

 RBT = rabbit

 HAM = hamster

 HMN = human

 MAM = mammal

 PGN = pigeon

 IVN = intravenous

 SCU = subcutaneous

 SKN = skin

 DRM = dermal

 OCC = ocular/corneal

 PCP = phycico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.