



SAFETY DATA SHEET

151 PILLAR BOX RED GLOSS PAINT - LOW VOC

Page: 1

Compilation date: 20/07/2010

Revision date: 14/08/2015

Revision No: 8

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: 151 PILLAR BOX RED GLOSS PAINT - LOW VOC

Product code: DY021A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: SU 21 - Consumer Uses.

PC9a: Coatings and paints, thinners, paint removers.

1.3. Details of the supplier of the safety data sheet

Company name: 151 Products Limited
The Old School House
39 Bengal Street
Manchester
M4 6AF
UK

Tel: 0161 839 5949

Fax: 0161 839 5493

Email: fereshteh@151.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Asp. Tox. 1: H304; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335

Most important adverse effects: Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H226: Flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H335: May cause respiratory irritation.
H412: Harmful to aquatic life with long lasting effects.

[cont...]

SAFETY DATA SHEET

151 PILLAR BOX RED GLOSS PAINT - LOW VOC

Page: 2

Hazard pictograms: GHS02: Flame
GHS07: Exclamation mark
GHS08: Health hazard



Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P264: Wash hands & exposed skin thoroughly after handling.
P280: Wear protective gloves.
P273: Avoid release to the environment.
P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/NHS111.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+233: Store in a well-ventilated place. Keep container tightly closed.
P501: Dispose of contents/container to Local Authority regulations.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

IRON (III) OXIDE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
215-168-2	1309-37-1	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319; STOT SE 3: H335	10-25%

LOW BOILING POINT NAPHTHA - UNSPECIFIED - STODDARD SOLVENT

232-489-3	8052-41-3	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	10-25%
-----------	-----------	---	---	--------

XYLENE

215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	3-5%
-----------	-----------	---	--	------

[cont...]

SAFETY DATA SHEET

151 PILLAR BOX RED GLOSS PAINT - LOW VOC

Page: 3

BARIUM SULPHATE

231-784-4	7727-43-7	Substance with a Community workplace exposure limit.	-	3-5%
-----------	-----------	--	---	------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Get immediate medical attention.

Inhalation: Move to fresh air in case of accidental inhalation of vapours.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

[cont...]

SAFETY DATA SHEET

151 PILLAR BOX RED GLOSS PAINT - LOW VOC

Page: 4

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Do not eat, drink or smoke when using this product. Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. KEEP OUT OF THE REACH OF CHILDREN.

Suitable packaging: * Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

IRON (III) OXIDE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5mg/m3	10mg/m3	-	-

XYLENE

UK	220 mg/m3	441 mg/m3	-	-
----	-----------	-----------	---	---

BARIUM SULPHATE

UK	-	-	4mg/m3	-
----	---	---	--------	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: No special requirements under normal conditions of use. In case of insufficient ventilation, wear an approved respirator gas/vapour filter Type A, organic vapours (EN141).

[cont...]

SAFETY DATA SHEET

151 PILLAR BOX RED GLOSS PAINT - LOW VOC

Page: 5

Hand protection: Protective gloves.

Eye protection: Safety glasses.

Skin protection: No special requirements under normal conditions of use.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Red

Odour: Characteristic odour

Solubility in water: * Insoluble

Viscosity: Viscous

Kinematic viscosity: 7.5cm²/s

Flash point°C: 25

Relative density: 0.95

VOC g/l: 293

9.2. Other information

Other information: * EU Limit value for this product (Cat A/e): 400g/L

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

[cont...]

SAFETY DATA SHEET

151 PILLAR BOX RED GLOSS PAINT - LOW VOC

Page: 6

Hazardous ingredients:

IRON (III) OXIDE

ORAL	RAT	LD50	>5000	mg/kg
------	-----	------	-------	-------

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

BARIUM SULPHATE

ORAL	RAT (Male)	LD50	>5000	mg/kg
------	------------	------	-------	-------

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

IRON (III) OXIDE

ALGAE (Aphanizomenon flos-aquae)	16H EC50	>8.5	mg/l
DAPHNIA (Daphnia magna)	96H LC50	>100	mg/l
ZEBRAFISH (Brachydanio rerio)	96H LC0	>50	g/l
ZEBRAFISH (Brachydanio rerio)	96H LC90	100	g/l

[cont...]

SAFETY DATA SHEET

151 PILLAR BOX RED GLOSS PAINT - LOW VOC

Page: 7

XYLENE

Daphnia magna	IC50	2.2	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50 (Read across)	2.6	mg/l

BARIUM SULPHATE

Daphnia magna	48H EC50	14500	µg/l
ZEBRAFISH (Brachydanio rerio)	96H LC50	>152	mg/l

12.2. Persistence and degradability

Persistence and degradability: * Not readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: * No data available.

12.4. Mobility in soil

Mobility: * Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: * Harmful to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Disposal should be in accordance with Local Authority Regulations.

Disposal of packaging: Disposal should be in accordance with Local Authority Regulations.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT
(LOW BOILING POINT NAPHTHA - UNSPECIFIED - STODDARD SOLVENT)

14.3. Transport hazard class(es)

Transport class: 3

[cont...]

SAFETY DATA SHEET

151 PILLAR BOX RED GLOSS PAINT - LOW VOC

Page: 8

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: A REACH registration number is not applicable as this product is a mixture.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.