



# 151 PILLAR BOX RED GLOSS PAINT - LOW VOC

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Issue date: 7/20/2010 Revision date: 5/24/2023 Supersedes version of: 6/27/2022 Version: 10.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : 151 PILLAR BOX RED GLOSS PAINT - LOW VOC  
UFI : AJP1-M0XR-P007-NYCM  
Product code : DY021A, DY052  
Type of product : Paint  
Product group : End product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Consumer use

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

151 Products Limited  
The Old School House 39 Bengal Street  
UK– M4 6AF Manchester  
United Kingdom  
T +44(0)161 839 5949 - F +44(0)161 839 5993  
[Technical@151products.com](mailto:Technical@151products.com)

##### Distributor

151 Products Limited  
The Old School House 39 Bengal Street  
UK– M4 6AF Manchester  
United Kingdom  
T +44(0)161 839 5949 - F +44(0)161 839 5993  
[Technical@151products.com](mailto:Technical@151products.com)

#### 1.4. Emergency telephone number

Emergency number : +44(0)161 839 5949  
During Office Hours (09:00 - 17:00). For outside office hours contact  
[Technical@151products.com](mailto:Technical@151products.com)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226  
Specific target organ toxicity – Repeated exposure, Category 1 H372  
Aspiration hazard, Category 1 H304  
Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. Causes damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

# 151 PILLAR BOX RED GLOSS PAINT - LOW VOC


## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: STODDARD SOLVENT

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.

H304 - May be fatal if swallowed and enters airways.

H372 - Causes damage to organs through prolonged or repeated exposure.

Precautionary statements (CLP)

: P102 - Keep out of reach of children.

P103 - Read label before use.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P270 - Do not eat, drink or smoke when using this product.

P280 - Wear protective gloves.

P264 - Wash hands thoroughly after handling.

P301+P330+P331+P310 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

Immediately call a doctor.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P101 - If medical advice is needed, have product container or label at hand.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P501 - Dispose of contents and container to local authority guidelines.

### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
STODDARD SOLVENT	CAS-No.: 8052-41-3 EC-No.: 232-489-3 EC Index-No.: 649-345-00-4	< 25	Muta. 1B, H340 Carc. 1A, H350 STOT RE 1, H372 Asp. Tox. 1, H304
XYLENE	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9	< 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315

Full text of H- and EUH-statements: see section 16

# 151 PILLAR BOX RED GLOSS PAINT - LOW VOC

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after ingestion	: Risk of lung oedema.
----------------------------------	------------------------

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

#### 5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray.
----------------------	--

##### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

# 151 PILLAR BOX RED GLOSS PAINT - LOW VOC

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

No additional information available

##### 8.1.2. Recommended monitoring procedures

No additional information available

##### 8.1.3. Air contaminants formed

No additional information available

##### 8.1.4. DNEL and PNEC

No additional information available

##### 8.1.5. Control banding

No additional information available

#### 8.2. Exposure controls

##### 8.2.1. Appropriate engineering controls

###### Appropriate engineering controls:

Ensure good ventilation of the work station.

##### 8.2.2. Personal protection equipment

###### Personal protective equipment symbol(s):



###### 8.2.2.1. Eye and face protection

###### Eye protection:

Safety glasses

###### 8.2.2.2. Skin protection

###### Skin and body protection:

Wear suitable protective clothing

# 151 PILLAR BOX RED GLOSS PAINT - LOW VOC

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Hand protection:

Protective gloves

### 8.2.2.3. Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: red.
Odour	: Characteristic odour.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Flammable liquid and vapour.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 25 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 0.95
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

# 151 PILLAR BOX RED GLOSS PAINT - LOW VOC

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified.
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.

#### STODDARD SOLVENT (8052-41-3)

STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
------------------------	---

Aspiration hazard : May be fatal if swallowed and enters airways.

### 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified.
Not rapidly degradable	

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

# 151 PILLAR BOX RED GLOSS PAINT - LOW VOC

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available



## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Additional information : Flammable vapours may accumulate in the container.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 1263	UN 1263	Not regulated	Not regulated	Not regulated
<b>14.2. UN proper shipping name</b>				
PAINT (Stoddard Solvent)	PAINT (Stoddard Solvent)	Not regulated	Not regulated	Not regulated
<b>Transport document description</b>				
UN 1263 PAINT (Stoddard Solvent), 3, III, (E)	UN 1263 PAINT (Stoddard Solvent), 3, III	Not regulated	Not regulated	Not regulated
<b>14.3. Transport hazard class(es)</b>				
3	3	Not regulated	Not regulated	Not regulated
		Not regulated	Not regulated	Not regulated
<b>14.4. Packing group</b>				
III	III	Not regulated	Not regulated	Not regulated
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Not regulated	Not regulated	Not regulated
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR) : F1  
Special provisions (ADR) : 163, 367, 650  
Limited quantities (ADR) : 5I  
Excepted quantities (ADR) : E1  
Packing instructions (ADR) : P001, R001  
Special packing provisions (ADR) : PP1

# 151 PILLAR BOX RED GLOSS PAINT - LOW VOC

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Mixed packing provisions (ADR)	: MP19
Transport category (ADR)	: 3
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: E
EAC code	: •3YE

### Transport by sea

Special provisions (IMDG)	: 163, 223, 367, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

### Air transport

Not regulated

### Inland waterway transport

Not regulated

### Rail transport

Not regulated

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

##### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

##### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)



# 151 PILLAR BOX RED GLOSS PAINT - LOW VOC

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 15.1.2. National regulations

#### France

Occupational diseases	
Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

#### Germany

Employment restrictions	: Observe restrictions according Act on the Protection of Working Mothers (MuSchG). Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
Water hazard class (WGK)	: WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).
Chemicals Prohibition Ordinance (ChemVerbotsV)	: This product is subject to ChemVerbotsV Annex 2 Entry 1. The following requirements must be observed: authorization requirement (according to § 6 paragraph 1 sentence 1), basic requirements for carrying out the delivery (according to § 8 paragraph 1, 3 and 4), identification and documentation (according to § 9 paragraph 1 to 3) and exclusion of the shipping route (according to § 10).
Hazardous Incident Ordinance (12. BImSchV)	: Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

#### Netherlands

SZW-lijst van kankerverwekkende stoffen	: STODDARD SOLVENT is listed
SZW-lijst van mutagene stoffen	: STODDARD SOLVENT is listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: XYLENE is listed

#### Denmark

Class for fire hazard	: Class II-1
Store unit	: 5 liter
Classification remarks	: R10 <H226;H304;H372>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

#### Switzerland

Storage class (LK)	: LK 3 - Flammable liquids
Chemicals Ordinance (SR 813.11)	: Group 2

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor

# 151 PILLAR BOX RED GLOSS PAINT - LOW VOC

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1A	Carcinogenicity, Category 1A

# 151 PILLAR BOX RED GLOSS PAINT - LOW VOC

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H340	May cause genetic defects.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
Muta. 1B	Germ cell mutagenicity, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.