

151 SILICONE SEALANT - WHITE

Page: 1

Compilation date: 21/02/2013

Revision date: 23/12/2015

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: 151 SILICONE SEALANT - WHITE

Product code: DY1001-SEL

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: SU 21 - Consumer Uses.

1.3. Details of the supplier of the safety data sheet

Company name: 151 Products Limited

The Old School House 39 Bengal Street Manchester

M4 6AF

UK

Tel: 0161 839 5949 **Fax:** 0161 839 5493

Email: fereshteh@151.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: -: EUH066

Most important adverse effects: Repeated exposure may cause skin dryness or cracking.

2.2. Label elements

Label elements:

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.

Precautionary statements: P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P103: Read label before use.

P264: Wash hands thoroughly after handling.

P501: Dispose of contents/container to Local authority regulations.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

151 SILICONE SEALANT - WHITE

Page: 2

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE

EINECS	CAS	PBT / WEL	CLP Classification	Percent	
265-148-2	64742-46-7	-	Asp. Tox. 1: H304; -: EUH066	10-25%	
DISTILLATES (DETROLELIM) HYDROTREATED LICHT					

DISTILLATES (PETROLEUM) HYDROTREATED LIGHT

265-149-8	64742-47-8	-	Asp. Tox. 1: H304; STOT SE 3: H336; -:	5-10%
			EUH066	

Contains: SLT 5431 Acetoxy Silicone

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.Ingestion: There may be irritation of the throat.

Inhalation: May cause irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Delayed / immediate effects: No data available.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

151 SILICONE SEALANT - WHITE

Page: 3

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-

side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate

method. Wash the spillage site with large amounts of water.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. KEEP OUT OF THE

REACH OF CHILDREN.

Suitable packaging: Should be kept in original packaging

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	5mg/m3	10mg/m3	-	-

DISTILLATES (PETROLEUM) HYDROTREATED LIGHT

EU	200mg/m3	-	-	-
----	----------	---	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

151 SILICONE SEALANT - WHITE

Page: 4

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: No special requirements under normal conditions of use. In case of insufficient

ventilation, wear an approved respirator gas/vapour filter Type A, organic vapours

(EN141).

Hand protection: Protective gloves.Eye protection: Safety glasses.Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste Colour: White

Odour: Irritating odour

Solubility in water: Insoluble

Relative density: 0.96

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids. Water.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

151 SILICONE SEALANT - WHITE

Page: 5

11.1. Information on toxicological effects

Hazardous ingredients:

DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE

DERMAL	RBT	LD50	>2000	mg/kg
DUST/MIST	RAT	4H LC50	4.6	mg/l
ORAL	RAT	LD50	>5000	mg/kg

DISTILLATES (PETROLEUM) HYDROTREATED LIGHT

DERMAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg
VAPOURS	RAT	4H LC50	>5.28	mg/l

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.Ingestion: There may be irritation of the throat.

Inhalation: May cause irritation.

Delayed / immediate effects: No data available.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Insoluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

151 SILICONE SEALANT - WHITE

Page: 6

13.1. Waste treatment methods

Disposal operations: Disposal should be in accordance with Local Authority Regulations. **Disposal of packaging:** Disposal should be in accordance with Local Authority Regulations.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: A REACH registration number is not applicable as this product is a mixture.

CE1292, DoP-5431, EN-15651-1:F-EXT-INT-CC

EN-15651-2; G-CC EN-15651-4:S

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H304: May be fatal if swallowed and enters airways.

H336: May cause drowsiness or dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.