

OUT & ABOUT WATERPROOFING SPRAY

Page: 1

Compilation date: 26/11/2014

Revision date: 12/12/2014

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: * OUT & ABOUT WATERPROOFING SPRAY

Product code: FM019

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: SU 21 - Consumer Uses.

1.3. Details of the supplier of the safety data sheet

Company name: 151 Products Limited

The Old School House 39 Bengal Street Manchester M4 6AF

101-4 07 (

UK

Tel: 0161 839 5949 **Fax:** 0161 839 5493

Email: fereshteh@151.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Flam. Aerosol 1: H222; Skin Irrit. 2:

H315; STOT SE 3: H336; -: H229

Classification under CHIP: F+: R12; Xi: R38; N: R50/53; -: R67

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin

irritation. May cause drowsiness or dizziness. Very toxic to aquatic life. Very toxic to

aquatic life with long lasting effects.

2.2. Label elements

Label elements under CLP:

Hazard statements: H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

[cont...]

OUT & ABOUT WATERPROOFING SPRAY

Page: 2

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark GHS09: Environmental







Precautionary statements: P211: Do not spray on an open flame or other ignition source.

P102: Keep out of reach of children.

P261: Avoid breathing mist. P280: Wear protective gloves.

P251: Pressurized container: Do not pierce or burn, even after use.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P312: Call a POISON CENTER or doctor if you feel unwell.

2.3. Other hazards

 $\begin{tabular}{ll} \textbf{Other hazards:} & \textbf{In use, may form flammable / explosive vapour-air mixture.} \end{tabular}$

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HEPTANE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
205-563-8	142-82-5	-	Flam. Liq. 2: H225; Asp. Tox. 1: H304; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Acute 1: H400; Aquatic Chronic 1: H410	30-50%

BUTANE

203-448-7	106-97-8	Substance with a Community	Flam. Gas 1: H220; Press. Gas: H280	10-30%
		workplace exposure limit.		

ISOBUTANE

200-857-2	75-28-5	Substance with a Community	Flam. Gas 1: H220; Press. Gas: H280	1-10%
		workplace exposure limit.		

OUT & ABOUT WATERPROOFING SPRAY

Page: 3

PROPANE

200-827-9	74-98-6	Substance with a Community	Flam. Gas 1: H220; Press. Gas: H280	1-10%
		workplace exposure limit.		

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Seek medical attention if irritation or other symptoms develop and persist.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. If patient feels unwell seek medical attention

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If irritation

persists seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the nose and upper respiratory tract. Solvent abuse can kill.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-

side up to prevent the escape of liquid.

OUT & ABOUT WATERPROOFING SPRAY

Page: 4

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep out of the reach of children.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

HEPTANE

Workplace exposure limits:

Respirable dust

•	•		•	
State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	2100 mg/m3	8400 mg/m3	-	-
BUTANE				
UK	1450 mg/m3	1810 mg/m3	-	-
ISOBUTANE				
UK	2400 mg/m3	9600 mg/m3	-	-
PROPANE				
UK	1800 mg/m3	7200 mg/m3	-	_

DNEL/PNEC Values

DNEL / PNEC No data available.

OUT & ABOUT WATERPROOFING SPRAY

Page: 5

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: No special requirements under normal conditions of use.

Hand protection: Impermeable gloves.

Eye protection: No special requirements under normal conditions of use. **Skin protection:** No special requirements under normal conditions of use.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol
Colour: Colourless

Odour: Perceptible odour

•

Solubility in water: Insoluble

Viscosity: Non-viscous

Boiling point/range°C: >50 Flash point°C: -4 (Liquid product)

Relative density: 0.7

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Direct sunlight.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

OUT & ABOUT WATERPROOFING SPRAY

Page: 6

11.1. Information on toxicological effects

Hazardous ingredients:

HEPTANE

IVIN	I۷	/N	MUS	LD50	222	mg/kg
------	----	----	-----	------	-----	-------

Relevant effects for mixture:

Effect	Route	Basis
Irritation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the nose and upper respiratory tract. Solvent abuse can kill.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable in part only.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Disposal should be in accordance with Local Authority Regulations. **Disposal of packaging:** Disposal should be in accordance with Local Authority Regulations.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

OUT & ABOUT WATERPROOFING SPRAY

Page: 7

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D
Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: A REACH registration number is not applicable as this product is a mixture.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

H229: Pressurised container: May burst if heated

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

R12: Extremely flammable.

OUT & ABOUT WATERPROOFING SPRAY

Page: 8

R38: Irritating to skin.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

Legend to abbreviations: PNEC = predicted no effect level

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = phycico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.