

151 PINK SPRAY PAINT

Page: 1

Compilation date: 17/07/2015 Revision date: 07/02/2017

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: 151 PINK SPRAY PAINT

Product code: * TAR015A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: SU 21 - Consumer Uses. PC9a: Coatings and paints, thinners, paint removers.

1.3. Details of the supplier of the safety data sheet

Company name: 151 Products Limited

The Old School House 39 Bengal Street Manchester M4 6AF UK Tel: 0161 839 5949 Fax: 0161 839 5493 Email: fereshteh@151.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319; Flam. Aerosol 1: H222; STOT SE 3: H336; -: H229

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes

serious eye irritation. May cause drowsiness or dizziness.

2.2. Label elements

Label elements:

Hazard statements:	H222: Extremely flammable aerosol.
	H229: Pressurised container: May burst if heated
	H319: Causes serious eye irritation.
	H336: May cause drowsiness or dizziness.
Hazard pictograms:	GHS02: Flame
	GHS07: Exclamation mark



151 PINK SPRAY PAINT

Signal words:	Danger
Precautionary statements:	P102: Keep out of reach of children.
	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking.
	P211: Do not spray on an open flame or other ignition source.
	P251: Do not pierce or burn, even after use.
	P261: Avoid breathing mist and spray.
	P264: Wash hands thoroughly after handling.
	P271: Use only outdoors or in a well-ventilated area.
	P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
	P501: Dispose of contents/container to Local authority regulations.
2.3. Other hazards	

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

DIMETHYL ETHER

EINECS	CAS	PBT / WEL	CLP Classification	Percent
204-065-8	115-10-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	25-50%

N-BUTYL ACETATE

204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336;	10-25%
			-: EUH066	

ACETONE

200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319;	5-10%
			STOT SE 3: H336; -: EUH066	

2-BUTOXYETHANOL

203-905-0	111-76-2	-	Acute Tox. 4: H332; Acute Tox. 4: H312;	3-5%
			Acute Tox. 4: H302; Eye Irrit. 2: H319;	
			Skin Irrit. 2: H315	

Page: 2

151 PINK SPRAY PAINT

Page: 3

ETHYL ACETATE

205-500-4	141-78-6	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319;	1-3%	
			STOT SE 3: H336; -: EUH066		

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing. There may be irritation of the nose and upper respiratory tract.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes. Vapour may travel considerable distance to source of ignition and flash back. Pressurized container may explode in the heat of a fire.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-

side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

151 PINK SPRAY PAINT

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. KEEP OUT OF THE REACH OF CHILDREN.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DIMETHYL ETHER

oosure limits:	Re	espirable dust	
8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
766 mg/m3	958 mg/m3	-	
TATE			
724 mg/m3	966 mg/m3	-	
1210 mg/m3	3620 mg/m3	-	
IANOL			
25 ppm	50 ppm	-	
TE			
200 ppm	400 ppm	-	
	8 hour TWA 766 mg/m3 TATE 724 mg/m3 1210 mg/m3 IANOL 25 ppm	8 hour TWA 15 min. STEL 766 mg/m3 958 mg/m3 TATE 724 mg/m3 724 mg/m3 966 mg/m3 1210 mg/m3 3620 mg/m3 IANOL 50 ppm	8 hour TWA 15 min. STEL 8 hour TWA 766 mg/m3 958 mg/m3 - TATE - - 724 mg/m3 966 mg/m3 - 1210 mg/m3 3620 mg/m3 - IANOL - -

DNEL/PNEC Values

DNEL / PNEC No data available.

151 PINK SPRAY PAINT

8.2. Exposure controls Engineering measures: Ensure there is sufficient ventilation of the area. Respiratory protection: In case of insufficient ventilation, wear an approved respirator gas/vapour filter Type A, organic vapours (EN141). Hand protection: Protective gloves. Eye protection: Safety glasses. Skin protection: No special requirements under normal conditions of use.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:AerosolColour:PinkOdour:Solvent.Solubility in water:InsolubleFlash point°C:-21

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

151 PINK SPRAY PAINT

Hazardous ingredients:

N-BUTYL ACETATE

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

2-BUTOXYETHANOL

IVN	RAT	LD50	307	mg/kg
ORL	MUS	LD50	1230	mg/kg
ORL	RAT	LD50	470	mg/kg

ETHYL ACETATE

ORL	MUS	LD50	4100	mg/kg
ORL	RAT	LD50	5620	mg/kg
SCU	RAT	LDLO	5	gm/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing. There may be irritation of the nose and upper respiratory tract.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

151 PINK SPRAY PAINT

Page: 7

ACETONE					
BLUEGILL (Lepomis macro	chirus)	LC50	8300	mg/l	
40.0 Develotion and develo					
12.2. Persistence and degradability					
Persistence and degradability: Partially biodegradable					
12.3. Bioaccumulative potential					
Bioaccumulative potential:	No data available.				
12.4. Mobility in soil					
Mobility:	Insoluble in water.				
12.5. Results of PBT and vPvB assessment					
PBT identification:	PBT identification: This product is not identified as a PBT/vPvB substance.				
12.6. Other adverse effects					
Other adverse effects:	Negligible ecotoxicity.				
Section 13: Disposal conside	erations				
13.1. Waste treatment metho	ds				
Disposal operations:	Dianocal should be in ano	ordonoo with Loool Au			
Disposal operations:	Disposal should be in accordance with Local Authority Regulations. Do not puncture				
Disposal of packaging:	containers prior to disposal.				
	Disposal should be in accordance with Local Authority Regulations. The user's attention is drawn to the possible existence of regional or national				
	regulations regarding disp				
Section 14: Transport inform					
14.1. UN number					
UN number:					
UN number:	ne				
UN number: 14.2. UN proper shipping nar	ne AEROSOLS				
UN number: 14.2. UN proper shipping nar Shipping name:	ne AEROSOLS (es)				
UN number: 14.2. UN proper shipping nar Shipping name: 14.3. Transport hazard class	ne AEROSOLS (es)				
UN number: 14.2. UN proper shipping nar Shipping name: 14.3. Transport hazard class Transport class:	ne AEROSOLS (es) 2				
UN number: 14.2. UN proper shipping nar Shipping name: 14.3. Transport hazard class Transport class: 14.4. Packing group	ne AEROSOLS (es) 2		Marine pollutant:	No	
UN number: 14.2. UN proper shipping nar Shipping name: 14.3. Transport hazard class Transport class: 14.4. Packing group 14.5. Environmental hazards	ne AEROSOLS (es) 2 No		Marine pollutant:	No	
UN number: 14.2. UN proper shipping nar Shipping name: 14.3. Transport hazard class Transport class: 14.4. Packing group 14.5. Environmental hazards Environmentally hazardous: 14.6. Special precautions for	ne AEROSOLS (es) 2 No		Marine pollutant:	No	
UN number: 14.2. UN proper shipping nar Shipping name: 14.3. Transport hazard class Transport class: 14.4. Packing group 14.5. Environmental hazards Environmentally hazardous: 14.6. Special precautions for	ne AEROSOLS (es) 2 No user No special precautions.		Marine pollutant:	No	
UN number: 14.2. UN proper shipping nar Shipping name: 14.3. Transport hazard classe Transport class: 14.4. Packing group 14.5. Environmental hazards Environmentally hazardous: 14.6. Special precautions for Special precautions:	ne AEROSOLS (es) 2 No user No special precautions. D		Marine pollutant:	No	

151 PINK SPRAY PAINT

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

ety data sheet is prepared in accordance with Commission Regulation (EU) No
0.
es text in the SDS which has changed since the last revision.
S: Repeated exposure may cause skin dryness or cracking.
xtremely flammable gas.
xtremely flammable aerosol.
lighly flammable liquid and vapour.
lammable liquid and vapour.
ressurised container: May burst if heated
larmful if swallowed.
larmful in contact with skin.
auses skin irritation.
causes serious eye irritation.
larmful if inhaled.
lay cause drowsiness or dizziness.
we information is believed to be correct but does not purport to be all inclusive
Il be used only as a guide. This company shall not be held liable for any
resulting from handling or from contact with the above product.