



SAFETY DATA SHEET

151 MULTIPURPOSE SPRAY PAINT - BLACK MATT

Page: 1

Compilation date: 08/06/2016

Revision date: 19/03/2020

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: 151 MULTIPURPOSE SPRAY PAINT - BLACK MATT

Product code: TAR025

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: SU 21 - Consumer Uses.

PC9a: Coatings and paints, thinners, paint removers.

1.3. Details of the supplier of the safety data sheet

Company name: 151 Products Ltd
The Old School House
39 Bengal Street
Manchester
M4 6AF
United Kingdom
Tel: +44 (0)161 839 5949
Fax: +44 (0)161 839 5493
Email: fereshteh@151.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0)161 839 5949
(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Aerosol 1: H222; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066; -: H229

Most important adverse effects: Repeated exposure may cause skin dryness or cracking. Extremely flammable aerosol.
Pressurised container: May burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness.

2.2. Label elements

Label elements:

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.
H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.

[cont...]

SAFETY DATA SHEET

151 MULTIPURPOSE SPRAY PAINT - BLACK MATT

Page: 2

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P261: Avoid breathing spray.

P264: Wash hands thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501: Dispose of contents/container to Local authority regulations.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

DIMETHYL ETHER

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|-----------|----------|--|-------------------------------------|---------|
| 204-065-8 | 115-10-6 | Substance with a Community workplace exposure limit. | Flam. Gas 1: H220; Press. Gas: H280 | 25-50% |

N-BUTYL ACETATE

| | | | | |
|-----------|----------|---|--|--------|
| 204-658-1 | 123-86-4 | - | Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066 | 10-25% |
|-----------|----------|---|--|--------|

[cont...]

SAFETY DATA SHEET

151 MULTIPURPOSE SPRAY PAINT - BLACK MATT

Page: 3

ETHYL ACETATE

| | | | | |
|-----------|----------|---|---|--------|
| 205-500-4 | 141-78-6 | - | Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066 | 10-25% |
|-----------|----------|---|---|--------|

CARBON BLACK

| | | | | |
|-----------|-----------|---|---|-------|
| 215-609-9 | 1333-86-4 | Substance with a Community workplace exposure limit. | - | 5-10% |
|-----------|-----------|---|---|-------|

ACETONE

| | | | | |
|-----------|---------|---|---|------|
| 200-662-2 | 67-64-1 | - | Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066 | 3-5% |
|-----------|---------|---|---|------|

2-BUTOXYETHANOL

| | | | | |
|-----------|----------|---|---|------|
| 203-905-0 | 111-76-2 | - | Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315 | 1-3% |
|-----------|----------|---|---|------|

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing. There may be irritation of the nose and upper respiratory tract. Solvent abuse can kill.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes. Vapour may travel considerable distance to source of ignition and flash back. Pressurized container may explode in the heat of a fire.

[cont...]

SAFETY DATA SHEET

151 MULTIPURPOSE SPRAY PAINT - BLACK MATT

Page: 4

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. KEEP OUT OF THE REACH OF CHILDREN.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

N-BUTYL ACETATE

Workplace exposure limits:

Respirable dust

| State | 8 hour TWA | | 15 min. STEL | |
|-------|-----------------------|-----------------------|--------------|--------------|
| | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
| UK | 724 mg/m ³ | 966 mg/m ³ | - | - |

[cont...]

SAFETY DATA SHEET

151 MULTIPURPOSE SPRAY PAINT - BLACK MATT

Page: 5

ETHYL ACETATE

| | | | | |
|----|---------|---------|---|---|
| UK | 200 ppm | 400 ppm | - | - |
|----|---------|---------|---|---|

ACETONE

| | | | | |
|----|------------------------|------------------------|---|---|
| UK | 1210 mg/m ³ | 3620 mg/m ³ | - | - |
|----|------------------------|------------------------|---|---|

2-BUTOXYETHANOL

| | | | | |
|----|--------|--------|---|---|
| UK | 25 ppm | 50 ppm | - | - |
|----|--------|--------|---|---|

DNEL/PNEC Values

Hazardous ingredients:

CARBON BLACK

| Type | Exposure | Value | Population | Effect |
|------|----------------------------|----------------------|------------|--------|
| DNEL | Inhalation (repeated dose) | 0.5mg/m ³ | Workers | Local |
| PNEC | Fresh water | 1mg/L | - | - |
| PNEC | Marine water | 0.1mg/L | - | - |

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: In case of insufficient ventilation, wear an approved respirator gas/vapour filter Type A, organic vapours (EN141).

Hand protection: Protective gloves.

Eye protection: Safety glasses.

Skin protection: No special requirements under normal conditions of use.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Black

Odour: Solvent.

Solubility in water: Insoluble

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

[cont...]

SAFETY DATA SHEET

151 MULTIPURPOSE SPRAY PAINT - BLACK MATT

Page: 6

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

N-BUTYL ACETATE

| | | | | |
|-----|-----|------|-------|-------|
| ORL | RAT | LD50 | 10768 | mg/kg |
|-----|-----|------|-------|-------|

ETHYL ACETATE

| | | | | |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 4100 | mg/kg |
| ORL | RAT | LD50 | 5620 | mg/kg |
| SCU | RAT | LDLO | 5 | gm/kg |

CARBON BLACK

| | | | | |
|--------|-----|------|----|------|
| DERMAL | RAT | LD50 | >8 | g/kg |
|--------|-----|------|----|------|

ACETONE

| | | | | |
|-----|-----|------|------|-------|
| IVN | RAT | LD50 | 5500 | mg/kg |
| ORL | MUS | LD50 | 3000 | mg/kg |
| ORL | RAT | LD50 | 5800 | mg/kg |

2-BUTOXYETHANOL

| | | | | |
|-----|-----|------|------|-------|
| IVN | RAT | LD50 | 307 | mg/kg |
| ORL | MUS | LD50 | 1230 | mg/kg |
| ORL | RAT | LD50 | 470 | mg/kg |

[cont...]

SAFETY DATA SHEET

151 MULTIPURPOSE SPRAY PAINT - BLACK MATT

Page: 7

Relevant hazards for product:

| Hazard | Route | Basis |
|-------------------------------|-------|-----------------------|
| Serious eye damage/irritation | OPT | Hazardous: calculated |
| STOT-single exposure | - | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing. There may be irritation of the nose and upper respiratory tract. Solvent abuse can kill.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

CARBON BLACK

| | | | |
|-------------------------|---------|-------|------|
| ZEBRAFISH (Danio rerio) | 96H LC0 | >1000 | mg/l |
|-------------------------|---------|-------|------|

ACETONE

| | | | |
|--------------------------------|------|------|------|
| BLUEGILL (Lepomis macrochirus) | LC50 | 8300 | mg/l |
|--------------------------------|------|------|------|

12.2. Persistence and degradability

Persistence and degradability: Partially biodegradable

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Insoluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Disposal should be in accordance with local authority regulations. Do not pierce containers prior to disposal.

[cont...]

SAFETY DATA SHEET

151 MULTIPURPOSE SPRAY PAINT - BLACK MATT

Page: 8

Disposal of packaging: Disposal should be in accordance with local authority regulations.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS, FLAMMABLE
(DIMETHYL ETHER)

14.3. Transport hazard class(es)

Transport class: 2.1

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H229: Pressurised container: May burst if heated.

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

[cont...]

SAFETY DATA SHEET

151 MULTIPURPOSE SPRAY PAINT - BLACK MATT

Page: 9

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.