

**CLEAR MATT VARNISH** 

Page: 1

Compilation date: 02/11/2018

Revision No: 1

# Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: CLEAR MATT VARNISH

Product code: TAR057

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: SU 21 - Consumer Uses.

# 1.3. Details of the supplier of the safety data sheet

Company name: 151 Products Ltd

The Old School House 39 Bengal Street Manchester M4 6AF

United Kingdom

Tel: +44 (0)161 839 5949

Fax: +44 (0)161 839 5493

Email: fereshteh@151.co.uk

# 1.4. Emergency telephone number

Emergency tel: +44 (0)161 839 5949

(office hours only)

#### Section 2: Hazards identification

# 2.1. Classification of the substance or mixture

Classification under CLP: Flam. Aerosol 1: H222; STOT SE 3: H336; -: EUH066; -: H229

Most important adverse effects: Repeated exposure may cause skin dryness or cracking. Extremely flammable aerosol.

Pressurised container: May burst if heated. May cause drowsiness or dizziness.

### 2.2. Label elements

# Label elements:

**Hazard statements:** EUH066: Repeated exposure may cause skin dryness or cracking.

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H336: May cause drowsiness or dizziness.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





# **CLEAR MATT VARNISH**

Page: 2

Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P261: Avoid breathing spray.

P264: Wash hands thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

Flam. Liq. 3: H226; STOT SE 3: H336;

-: EUH066

contact lenses, if present and easy to do. Continue rinsing.

P101: If medical advice is needed, have product container or label at hand.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501: Dispose of contents/container to Local authority regulations.

#### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

123-86-4

# 3.2. Mixtures

# Hazardous ingredients:

# DIMETHYL ETHER

EINECS	CAS	PBT / WEL	CLP Classification	Percent		
204-065-8	115-10-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	25-50%		
N-BUTYL ACETATE						

# TITANII INA DIOVIDE

204-658-1

THANIOM DIOXIDE						
236-675-5	13463-67-7	Substance with a Community	-	5-10%		
		workplace exposure limit.				

### ACETONE

200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319;	3-5%
			STOT SE 3: H336; -: EUH066	

10-25%

#### **CLEAR MATT VARNISH**

Page: 3

#### 2-BUTOXYETHANOL

203-905-0	111-76-2	-	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315	1-3%		
ETHYL ACETATE						
205-500-4	141-78-6	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-3%		

#### Section 4: First aid measures

# 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist

examination.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing. There may be irritation of the nose and

upper respiratory tract. Solvent abuse can kill.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

# Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

# 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes. Vapour may travel considerable distance to source of

ignition and flash back. Pressurized container may explode in the heat of a fire.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

# Section 6: Accidental release measures

**CLEAR MATT VARNISH** 

Page: 4

# 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

#### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

# Section 7: Handling and storage

## 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. KEEP OUT OF THE REACH OF CHILDREN.

Suitable packaging: Must only be kept in original packaging.

# 7.3. Specific end use(s)

Specific end use(s): No data available.

# Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

Workplace exposure limits: No data available.

#### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

# 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: In case of insufficient ventilation, wear an approved respirator gas/vapour filter Type A,

organic vapours (EN141).

Hand protection: Protective gloves.Eye protection: Safety glasses.

Skin protection: No special requirements under normal conditions of use.

#### Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Aerosol

**CLEAR MATT VARNISH** 

Page: 5

Colour: Clear

Odour: Solvent.

Solubility in water: Insoluble

Flash point°C: -21

#### 9.2. Other information

Other information: No data available.

# Section 10: Stability and reactivity

# 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Conditions to avoid: Heat. Sources of ignition. Flames.

# 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

# 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

# **Section 11: Toxicological information**

# 11.1. Information on toxicological effects

# **Hazardous ingredients:**

# **N-BUTYL ACETATE**

ORL RAT LD50 10768 mg/kg
--------------------------

# **TITANIUM DIOXIDE**

DUST/MIST	RAT	4H LC50	>3.43	mg/l
ORAL	RAT	LD50	>2000	mg/kg

### **ACETONE**

IVN	RΔT	LD50	5500	ma/ka
1 1 1 1	KAI	LDSG	0000	mg/kg

**CLEAR MATT VARNISH** 

Page: 6

ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

#### 2-BUTOXYETHANOL

IVN	RAT	LD50	307	mg/kg
ORL	MUS	LD50	1230	mg/kg
ORL	RAT	LD50	470	mg/kg

# **ETHYL ACETATE**

ORL	MUS	LD50	4100	mg/kg
ORL	RAT	LD50	5620	mg/kg
SCU	RAT	LDLO	5	gm/kg

#### Relevant hazards for product:

Hazard	Route	Basis
STOT-single exposure	-	Hazardous: calculated

# Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing. There may be irritation of the nose and

upper respiratory tract. Solvent abuse can kill.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# **Section 12: Ecological information**

# 12.1. Toxicity

# Hazardous ingredients:

# **ACETONE**

BLUEGILL (Lepomis macrochirus)	LC50	8300	mg/l
--------------------------------	------	------	------

# 12.2. Persistence and degradability

Persistence and degradability: No data available.

# 12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

#### 12.4. Mobility in soil

Mobility: Insoluble in water.

**CLEAR MATT VARNISH** 

Page: 7

#### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

Other adverse effects: No data available.

# Section 13: Disposal considerations

# 13.1. Waste treatment methods

Disposal operations: Disposal should be in accordance with local authority regulations. Do not pierce

containers prior to disposal.

Waste code number: 08 01 11

Disposal of packaging: Disposal should be in accordance with local authority regulations. Do not pierce

containers prior to disposal.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

#### **Section 14: Transport information**

#### 14.1. UN number

UN number: UN1950

# 14.2. UN proper shipping name

Shipping name: AEROSOLS, FLAMMABLE

(DIMETHYL ETHER)

# 14.3. Transport hazard class(es)

Transport class: 2.1

# 14.4. Packing group

### 14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

# 14.6. Special precautions for user

Special precautions: No special precautions.

# Section 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

# 15.2. Chemical Safety Assessment

# Section 16: Other information

# **CLEAR MATT VARNISH**

Page: 8

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H229: Pressurised container: May burst if heated.

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.